

AC140 Series

Low Cost, Miniature Industrial Multipurpose Accelerometer, Top Exit 2 Pin Mini-MIL Connector, 100 mV/g, ±15%



VIBRATION ANALYSIS HARDWARE



Product Features

Mini Industrial Accelerometer, Great for Hard-to-Reach Locations

- ▶ ± 80 g, Dynamic Range
- ▶ 2 Pin Mini-MIL Connection
- ▶ -6N Integral Cable Option Features Food-Safe, FDA-Compliant 21 CFR 177.1330 Polyolefin Heat Shrink

AC140-1D	AC140-2D	AC140-3D	AC140-6D	AC140-6N																																						
2 Pin Mini Mil Connector	CB110 Integral Cable	CB206 Armored Integral Cable	CB611 Heavy Duty Armored Integral Cable	CB111 Integral Cable																																						
<table border="1"> <tr><th>Connector Pin</th><th>Polarity</th></tr> <tr><td>A</td><td>(+)Signal/Power</td></tr> <tr><td>B</td><td>(-)Common</td></tr> </table>	Connector Pin	Polarity	A	(+)Signal/Power	B	(-)Common	<table border="1"> <tr><th>Conductor</th><th>Polarity</th></tr> <tr><td>Red</td><td>(+) Signal/Power</td></tr> <tr><td>Black</td><td>(-) Common</td></tr> <tr><td>Shield</td><td>Cable Drain Wire</td></tr> </table>	Conductor	Polarity	Red	(+) Signal/Power	Black	(-) Common	Shield	Cable Drain Wire	<table border="1"> <tr><th>Conductor</th><th>Polarity</th></tr> <tr><td>Red</td><td>(+) Signal/Power</td></tr> <tr><td>Black</td><td>(-) Common</td></tr> <tr><td>Shield</td><td>Cable Drain Wire</td></tr> </table>	Conductor	Polarity	Red	(+) Signal/Power	Black	(-) Common	Shield	Cable Drain Wire	<table border="1"> <tr><th>Conductor</th><th>Polarity</th></tr> <tr><td>Red</td><td>(+) Signal/Power</td></tr> <tr><td>Black</td><td>(-) Common</td></tr> <tr><td>Shield</td><td>Cable Drain Wire</td></tr> </table>	Conductor	Polarity	Red	(+) Signal/Power	Black	(-) Common	Shield	Cable Drain Wire	<table border="1"> <tr><th>Conductor</th><th>Polarity</th></tr> <tr><td>Red</td><td>(+) Signal/Power</td></tr> <tr><td>Black</td><td>(-) Common</td></tr> <tr><td>Shield</td><td>Cable Drain Wire</td></tr> </table>	Conductor	Polarity	Red	(+) Signal/Power	Black	(-) Common	Shield	Cable Drain Wire
Connector Pin	Polarity																																									
A	(+)Signal/Power																																									
B	(-)Common																																									
Conductor	Polarity																																									
Red	(+) Signal/Power																																									
Black	(-) Common																																									
Shield	Cable Drain Wire																																									
Conductor	Polarity																																									
Red	(+) Signal/Power																																									
Black	(-) Common																																									
Shield	Cable Drain Wire																																									
Conductor	Polarity																																									
Red	(+) Signal/Power																																									
Black	(-) Common																																									
Shield	Cable Drain Wire																																									
Conductor	Polarity																																									
Red	(+) Signal/Power																																									
Black	(-) Common																																									
Shield	Cable Drain Wire																																									
	Built To Order	Built To Order	Built To Order	Built To Order																																						

Specifications	Standard	Metric	Specifications	Standard	Metric
Part Number	AC140	M/ or M8/AC140	Environmental		
Sensitivity (±15%)	100 mV/g		Operating Temperature Range	-58 to 250 °F	-50 to 121 °C
Frequency Response (±3dB)	36-900,000 CPM	0.6-15000 Hz	Maximum Shock Protection	5,000 g, peak	
Dynamic Range	± 80 g, peak		Electromagnetic Sensitivity	CE	
Electrical			Sealing	Welded, Hermetic	
Settling Time	<2.5 seconds		Submersible Depth	200 ft.	60 m
Voltage Source	18-30 VDC		SIL Rating	SIL 2	
Constant Current Excitation	2-10 mA		Physical		
Spectral Noise @ 10 Hz	30 µg/√Hz		Sensing Element	PZT Ceramic	
Spectral Noise @ 100 Hz	4 µg/√Hz		Sensing Structure	Shear Mode	
Spectral Noise @ 1000 Hz	2 µg/√Hz		Weight	0.7 oz	20 grams
Output Impedance	<100 ohm		Case Material	316L Stainless Steel	
Bias Output Voltage	10-14 VDC		Mounting Thread	1/4-28 Blind Tapped Hole	
Case Isolation	>10 ⁹ ohm		Connector (Non-Integral)	2 Pin mini-MIL (J Series)	
			Resonant Frequency	2,040,000 CPM	34000 Hz
			Mounting Torque	2 to 5 ft. lbs.	2,7 to 6,8 Nm
			Mounting Hardware Supplied	1/4-28 Stud	M6x1 or M8x1.25 Adapter Stud
			Calibration Certificate	CA10	

Typical Frequency Response

